

Cabinet Liner

Specifications



	WHITE CABINET LINER	BLACK CABINET LINER
ORIGIN	China	China
SPECIES	Poplar	Poplar
CORE	Poplar	Poplar
FACE/BACK	HPL, Softwood Veneer	HPL, Softwood Veneer
FINISH	White	Black
SIDES	1-Side, 2-Side	1-Side, 2-Side
SIZE	48" x 96"	48" x 96"
HPL THICKNESS	0.5mm	0.5mm
GLUE TYPE	Interior, TSCA Title VI	Interior, TSCA Title VI
MOISTURE CONTENT	<12%	<12%
APPLICATIONS	Cabinet box construction, as well as casing and shelving	Cabinet box construction, as well as casing and shelving



	5.2MM	12MM	15MM	18MM
WHITE CABINET LINER				
# OF PLYS	5	9	11	13
THICKNESS VARIATION	4.8mm-5.2mm	11.5mm-12.3mm	14.5mm-15.3mm	17.5mm-18.3mm
SHEETS PER CRATE	180	78	62	52
BLACK CABINET LINER				
# OF PLYS		9		13
THICKNESS VARIATION		11.5mm-12.3mm		17.5mm-18.3mm
SHEETS PER CRATE		78		52

PER THE REQUIREMENTS OF THE ASTM E84-2022 STANDARD TEST METHOD FOR SURFACE BURNING CHARACTERISTICS OF BUILDING MATERIALS, THE CABINET LINER WE SOURCE HAS A FLAME SPREAD INDEX (FSI) OF 20 AND A SMOKE DEVELOPED INDEX (SDI) OF 25, GIVING THIS PRODUCT A CLASS A FIRE RATING.



Based on availability, USply reserves the right to substitute product that may vary in species, core, country of origin, and/or other specifications.